

SPECIFICATIONS

DIMENSIONS

Overall length
Overall width
Overall height
Wheelbase
Ground clearance

WEIGHT

Dry weight

CAPACITIES

Engine oil

Fuel tank
Fuel reserve
Cooling system capacity
Passenger capacity load
Maximum weight capacity

2,035 mm (80.1 in)
705 mm (27.8 in)
1,025 mm (40.4 in)
1,370 mm (53.9 in)
130 mm (5.1 in)

170.0 kg (374.8 lbs)

3.1 ♀ (3.3 US qt, 2.7 imp qt) After disassembly
2.9 ♀ (3.1 US qt, 2.6 imp qt) After draining

11.5 ♀ (3.04 US gal, 2.53 imp gal)
3.5 ♀ (0.92 US gal, 0.77 imp gal)
2.0 ♀ (0.53 US gal, 0.44 imp gal)
Operator and one passenger
157 kg (347 lbs)

ENGINE

Bore and stroke
Compression ratio
Displacement
Spark plug
Standard

For extended high speed
riding

Spark plug gap
Idle speed

Valve clearance(cold) Intake
Exhaust

55.0 × 42.0mm (2.16 × 1.65in)
11.5:1
399 cm³ (24.3 cu-in)
CR8EH-9 (NGK)
U24FER-9 (ND)
CR9EH-9 (NGK)
U27FER-9 (ND)
0.8- 0.9 mm (0.03- 0.04 in)
1,300±100rpm
1,400±100rpm (Caltif. model)
0.08 mm (0.003 in)
0.08 mm (0.003 in)
0.08 mm (0.003 in)